



SIZE CHART

Bronco II® Insulation Tube & Pipe Saddle

Key Features:

- Universal mounting feature allows secure fit on either side of channel
- Molded with self-tapping screw location hole
- UL Classified 2043 (25/50) for use in plenums and air handling systems
- Manufactured from high-strength Polypropylene Copolymer
- Extra strength ribbed side walls
- No assembly or tools required
- Enhanced safety lip prevents insulation crushing and tearing from pipe movement
- UV Resistant
- Available in black or white to match insulation
- Excellent finished appearance
- Made in the U.S.A.



COPPER TUBE OD SIZE	INSULATION THICKNESS				
	1/2"	3/4"	1"	1-1/2"	2"
3/8"	225B2S	225B2S	325B2S	425B2S	525B2S
1/2"	225B2S	225B2S	325B2S	425B2S	525B2S
5/8"	225B2S	225B2S	325B2S	425B2S	525B2S
3/4"	225B2S	325B2S	325B2S	425B2S	525B2S
7/8"	225B2S	325B2S	325B2S	425B2S	525B2S
1-1/8"	225B2S	325B2S	325B2S	425B2S	525B2S
1-3/8"	325B2S	325B2S	425B2S	525B2S	625B2S
1-5/8"	325B2S	325B2S	425B2S	525B2S	625B2S
2-1/8"	325B2S	425B2S	425B2S	525B2S	625B2S
2-5/8"	425B2S	425B2S	525B2S	625B2S	825B2S
3-1/8"	425B2S	525B2S	525B2S	625B2S	825B2S
3-5/8"	525B2S	525B2S	625B2S	825B2S	825B2S
4-1/8"	525B2S	625B2S	625B2S	825B2S	825B2S

Available in black (B) or white (W) to match insulation.

SCH. 40/80 PIPE	INSULATION THICKNESS				
	1/2"	3/4"	1"	1-1/2"	2"
1/4"	225B2S	225B2S	325B2S	425B2S	525B2S
3/8"	225B2S	225B2S	325B2S	425B2S	525B2S
1/2"	225B2S	325B2S	325B2S	425B2S	525B2S
3/4"	225B2S	325B2S	325B2S	425B2S	525B2S
1"	325B2S	325B2S	425B2S	525B2S	625B2S
1-1/4"	325B2S	325B2S	425B2S	525B2S	625B2S
1-1/2"	325B2S	425B2S	425B2S	525B2S	625B2S
2"	425B2S	425B2S	425B2S	525B2S	625B2S
2-1/2"	425B2S	525B2S	525B2S	625B2S	825B2S
3"	525B2S	525B2S	625B2S	825B2S	825B2S
3-1/2"	525B2S	625B2S	625B2S	825B2S	825B2S
4"	525B2S	625B2S	825B2S	825B2S	825B2S

Available in black (B) or white (W) to match insulation.