



Klo-Shure® Strut Mounted Coupling 4-1/8" O.D. x 1-1/2" Wall Insulation



Key Features

- UL Classified 2043 (25/50) for use in plenums and air handling systems.
- Superior vapor barrier at suspension points.
- Eliminate shock and vibration.
- Three times faster installation of closed-cell or elastomeric insulation than traditional methods.
- Dramatically improved finished appearance of insulated tubing.
- Eliminates insulation compression at suspension points.
- All metal components have a Trivalent (non-hex) plating.
- Available in 304 and 316 stainless steel.
- For use with strut mounted clamps.
- Available for 1/4" to 4-1/8" O.D. tube.
- Insulation wall thickness sizes include:
3/8"; 1/2"; 3/4"; 1" and 1-1/2".
- Molded with high strength Thermoplastic Olefin(TPO).
- Temperature rating: -60°F to +225°F



PART NO.

DESCRIPTION

729412

4-1/8" O.D. x 1-1/2" wall insulation

AVAILABLE NOW!

You ask, we listen!

We are proud to announce an additional size added to our 7- Series Klo-Shure Strut Mounted Insulation Coupling: 4-1/8" O.D. x 1-1/2" wall insulation

We continually seek opportunities to design engineered solutions to resolve your challenges. How can we help you?



1751 Summit Drive ■ Auburn Hills, Michigan 48326 ■ (248) 373-5151

Hydra-Zorb.com